

# SLOAN®

## CONCEALED SERIES – INWALL/INCEILING FLUSH VALVES



### Model 950 - Product Code 42001M

Mains Pressure - for W.Cs.

Minimum water supply pressure : 170 Kpa

Maximum water supply pressure : 700 Kpa

Flush volume : 6 Litres (optional 4.5 Litres)

Flow Rate Requirement : 1.0 Litre per second)

Inlet Connection Size : 25mm BSP.

### Model 995 - Product Code 42013M

Mains Pressure - for Wall Hung Urinals

Minimum water supply pressure : 170 Kpa

Maximum water supply pressure : 700 Kpa

Note: For certain brands of "Open Rim Urinals", the optimum pressure is 250 Kpa - This is achieved by installing a "Flomatic" adjustable pressure reducing valve.

Flush volume : 3 Litres (optional 1.9 Litres)

Flow Rate Requirement : 1.0 Litre per second)

Inlet Connection Size : 20mm BSP.

### Model 995 - Product Code 42014M

Mains Pressure - for Slab Type Urinals

Minimum water supply pressure : 170 Kpa

Maximum water supply pressure : 700 Kpa

Flush volume : 6 Litres (optional 4.5 Litres)

For every 1.8 Metres of Urinal Length

Flow Rate Requirement : 1.0 Litre per second)

Inlet Connection Size : 20mm BSP.

### Model 950 - Product Code 42006L


Tank Fed Pressure - for W.Cs.

Minimum water supply pressure : 4 Metres Head or 40 KPA.

Maximum water supply pressure : 40 Meters Head or 400 Kpa

Flush volume : 6 Litres (optional 4.5 Litres)

Inlet Connection Size : 40mm BSP.



### Model 995 - Product Code 42021L

Tank Fed Pressure - for Wall Hung Urinals

Minimum water supply pressure : 4 Metres Head or 40 KPA.

Maximum water supply pressure : 40 Meters Head or 400 Kpa

Flush volume : 3 Litres (optional 1.9 Litres)